



FIBERGLASS ROOFING FABRIC 190(100)

Specification	Unit	Value
Area Weight	g/sqm	190±10%
Width	cm	100
Loss on Ignition	%	7-15
Yarn Count per 10 cm Warp Weft	pcs	75-85 20-30
Tensile Strength MD	N/50 mm	≥1,000
Tensile Strength CD	N/50 mm	≥1,000
Color		White
Roll length	m	2,000

Fiberglass roofing fabric is a reinforced fiberglass fabric designed as a base for roll roofing and waterproofing materials. It is used in new and repaired roofs of any configuration, as well as in waterproofing concrete structures, pipelines, bridges, and foundations, performing reliably across a wide temperature range and in diverse climates.

Made from high-quality E-glass yarns and treated with a polymer emulsion, it offers excellent strength, dimensional stability, adhesion to bitumen binders, and resistance to decay. The material ensures durability, structural reliability, and consistent performance, making it a trusted choice for advanced roofing and waterproofing systems.

Heller GmbH
Glindfeld 14
D - 59964 Medebach
T +49 2982-92799 60
F +49 2982-92799 88

Geschäftsführer
Dr. Sophia-Antonia Heller
Jürgen Huber-Heller
info@heller-handel.de
www.heller-handel.de

Bankverbindung
Sparkasse Waldeck-Frankenberg
BIC: HELADEF1KOR
IBAN: DE76 5235 0005 0000 1057 00

Amtsgericht Arnshausen HRB 12375
USt.-ID-Nr. DE 226 273 283
EORI-Nr. DE 4 853 482
Steuer-Nr. 309/5722/0750